



INTRODUCTION

The Baicells Neutrino430 is an advanced two-carrier indoor eNodeB (eNB) compliant with 3GPP LTE TDD technology. This 4x250 mW eNB operates in either Carrier Aggregation (CA) mode or Dual Carrier (DC) mode.

In CA mode, the Neutrino430 supports 2CC (2 Component Carriers) DL/UL CA. 2CC DL/UL CA doubles DL/UL peak throughput compared to a single carrier by aggregating two separate spectrum resources into a virtual contiguous spectrum resource.

In DC mode, each carrier is treated as an independent cell, supporting 128+128 users, with each cell supporting 5, 10, 15, or 20 MHz bandwidth. Using a Neutrino430 in DC mode simplifies and streamlines the deployment of split sectors.

In addition, HaloB (an embedded EPC option) is available on the Neutrino430 as part of the basic software. The Baicells patented HaloB solution migrates the necessary core network functions to the eNB.

This product has a standard one-year warranty; an extended warranty is available.

HIGHLIGHTS

NOTE: Features can vary based on model or region.

- Standard LTE TDD Band 48
 - Customization can be requested:
 - Email sales_na@baicells.com for North America.
 - Email contact@baicells.com for all other regions.
- GUI-based local and remote Web management
- Compact, all-in-one design of internal antenna
- Excellent Non-Line-of-Sight (NLOS) coverage
- Peak rate for DL: Up to 290 Mbps with 2x20 MHz bandwidth
- Peak rate for UL: Up to 70 Mbps with 2x20 MHz bandwidth
- 2CC DL/UL CA improves the spectrum efficiency of fragmented spectrum resources
- Suitable for private and public deployments; any IP-based backhaul can be used, including public transmission protected by Internet Protocol Security (IPsec)
- 128 RRC connected users per carrier, 128+128 in DC mode, upgradeable to higher capacity in future releases
- Integrated small cell form factor for quick and easy installation
- Configured out-of-the-box to work with Baicells CloudCore
- HaloB as embedded EPC solution
- Supports Citizens Broadband Radio Service (CBRS) with proxy/direct Spectrum Access System (SAS)
- Supports Multi Operator Radio Access Network (MORAN)
- Support static Inter Cell Interference Coordination (ICIC)
- Plug-and-play with Self-Organizing Network (SON) capabilities
- Interoperable with standard LTE Evolved Packet Core (EPC)
- Supports TR-069 network management interface

TECHNOLOGY

Standard	LTE TDD RAN (3GPP Release 15 compliant)
TDD UL/DL Configuration	1, 2, 6 (with Special Subframe Configuration 7)
Frequency Band	B48 (3550 MHz–3700 MHz)
Channel Bandwidth	SC: 5/10/15/20 MHz CA: 40 MHz as maximum aggregated bandwidth
Multiplexing	MIMO: 2x2 (DL)
Security	Radio: SNOW 3G/AES-128 Backhaul: IPsec (X.509 AES-128, AES-256, SHA-128, SHA-256)

INTERFACE

Ethernet Interface	1 optical (SFP) and 1 RJ-45 Ethernet interface (1 GE)
Power Supply	12 VDC 2 A, PoE+/48 V 0.6 A, complies with IEEE 802.3at standard
Protocols Used	IPv4/IPv6 (Dual Stack), UDP, TCP, ICMP, SNMPv2c, NTP, SSH, IPsec, TR-069, HTTP/HTTPS, 1588v2, DHCP
Network Management	IPv4/IPv6, HTTP/HTTPS, SNMPv2c, TR-069, SSH, Embedded EPC
VLAN/VxLAN	802.IQ/VxLAN
LED Indicators	4 x status LED CELL1/CELL2/ALM/PWR

PERFORMANCE

	2x20 MHz	DL (Mbps)	UL (Mbps)
	Peak Data Rate (DC)	UL/DL Config 1	2x105
UL/DL Config 2		2x145	2x14
UL/DL Config 6		2x85	2x35
2x10 MHz		DL (Mbps)	UL (Mbps)
UL/DL Config 1		2x51	2x14
UL/DL Config 2		2x70	2x7
UL/DL Config 6		2x42	2x17
Peak Data Rate (CA)	2x20 MHz	DL (Mbps)	UL (Mbps)
	UL/DL Config 1	210	56
	UL/DL Config 2	290	28
	UL/DL Config 6	170	70
	2x10 MHz	DL (Mbps)	UL (Mbps)
	UL/DL Config 1	102	28
	UL/DL Config 2	140	14
UL/DL Config 6	84	34	

	20 MHz + 10 MHz	DL (Mbps)	UL (Mbps)
	UL/DL Config 1	156	42
	UL/DL Config 2	215	21
	UL/DL Config 6	127	52
	20 MHz + 15 MHz	DL (Mbps)	UL (Mbps)
	UL/DL Config 1	182	49
	UL/DL Config 2	250	24
	UL/DL Config 6	148	61
User Capacity	Up to 128 RRC connected users per cell (4 users per TTI) <ul style="list-style-type: none"> • SC/CA: 128 RRC connected users • DC: 128+128 RRC connected users 		
Latency	30 milliseconds		
Receive Sensitivity	-100 dBm (per channel)		
Modulation	MCS0 (QPSK) to MCS27 (256 QAM) DL: QPSK, 16 QAM, 64 QAM, 256 QAM UL: QPSK, 16 QAM, 64 QAM		
Transmit Power Range	0 to 24 dBm per channel (combined +30 dBm, configurable) (1 dB interval)		
Quality of Service	Nine-level priority indicated by QoS Class Identifiers (QCI)		
ARQ/HARQ	Supported		
Synchronization	GPS, 1588v2 (default)		

MODULATION LEVELS (TDD 2:7)

MCS	Modulation Scheme	RSRP (dBm)
0–4	QPSK	$-120 \leq \text{RSRP} < -110$
5–9	16 QAM	$-110 \leq \text{RSRP} < -100$
10–19	64 QAM	$-100 \leq \text{RSRP} < -85$
20–27	256 QAM	$\text{RSRP} \geq -85$

NOTE: The information provided is for reference only, as the environment can impact modulation levels.

FEATURES

Voice	VoLTE*
NSA	Supported
SON	Self-Organizing Network <ul style="list-style-type: none"> • Automatic setup • Automatic Neighbor Relation (ANR) • PCI confliction detection
EPC	HaloB (Embedded EPC)
Traffic Offload	Local breakout
Layer 2 Support	Transparent Bridge Mode

Maintenance	<ul style="list-style-type: none"> • Local/Remote Web maintenance • Online status management • Performance statistics • Fault management • Local/Remote software upgrade • Logging • Connectivity diagnosis • Automatic start and configuration • Alarm reporting • User information tracing • Signaling trace
--------------------	---

* Planned for future release.

LINK BUDGET

RF Antenna	3 dBi built-in omni antenna
GPS Antenna	External GPS antenna, SMA connector
Maximum EIRP	33 ± 1 dBm
Power Control	UL Open-loop/Closed-loop Power Control, DL Power Allocation (3GPP TS 36.213 compliant)

PHYSICAL


MTBF	≥ 150000 hours
MTTR	≤ 1 hour
Operating Temperature	23°F to 113°F / -5°C to 45°C
Storage Temperature	14°F to 122°F / -10°C to 50°C
Humidity	5% to 95% RH
Atmospheric Pressure	70 kPa to 106 kPa
Power Consumption	≤ 20 W
Weight	3.3 lb/1.5 kg
Dimensions (HxWxD)	8.7 x 8.7 x 1.9 inches 220 x 220 x 48 millimeters
Installation	Ceiling or wall mount

MODEL NUMBER


pBS31010	<p>Neutrino430 Indoor TDD eNB – LTE Release 15, 4x250 mW (24 dBm), 1 GE+1 OPT, 3 dBi built-in antenna, 3.5 GHz (3550 MHz–3700 MHz), B48</p> <ul style="list-style-type: none"> • FCC Certification: 2AG32PBS31010 • IC Certification: 20982-PBS31010
-----------------	--

NOTE: Customized versions can be requested.

ANTENNA PATTERN



H-Pattern



V-Pattern